

US EPA ARCHIVE DOCUMENT

EPA's Greenhouse Gas Reporting Program & Geologic Sequestration

Mike Kolian
Climate Change Division
U.S. Environmental Protection Agency

Progress Review of Star Grant Research on Carbon Geosequestration
January 7-8, 2013



This presentation is provided solely for informational purposes. It does not provide legal advice, have legally binding effect, or expressly or implicitly create, expand, or limit any legal rights, obligations, responsibilities, expectations, or benefits in regard to any person.



Overview of the GHG Reporting Program



Goal of GHG Reporting Program: To collect accurate GHG data to inform future policy decisions

- Covers 41 source categories for reporting
 - 33 types of direct emitters
 - 6 types of suppliers of fuel and industrial GHG
 - Facilities that inject CO₂ underground for geologic sequestration, enhanced oil recovery, or any other purpose
- 25,000 metric tons CO₂ equivalent (CO₂e) or more per year reporting threshold for most sources
- Reporting only, no control or use requirements
- Monitoring began in 2010 for 29 source categories and an additional 12 source categories began collecting data in 2011



Source Categories Covered by GHG Reporting Program




| Power | Refining & Petrochem | Other Chemicals | Combustion | Waste | Metals | Minerals | Pulp & Paper | High GWP Gases |
|--|---|---|---|--|--|---|--|---|
| <ul style="list-style-type: none"> - Electricity Generation - Electrical Equipment Mfg. - Electrical Equipment Use | <ul style="list-style-type: none"> - Petroleum Refineries - Petrochem. Production | <ul style="list-style-type: none"> - Adipic Acid - Ammonia - Hydrogen Production - Nitric Acid - Phosphoric Acid - Titanium Dioxide | <ul style="list-style-type: none"> - Stationary Combustion | <ul style="list-style-type: none"> - Industrial Waste Landfills - Industrial Wastewater Treatment - MSW Landfills | <ul style="list-style-type: none"> - Aluminum - Ferroalloy - Iron & Steel - Lead - Magnesium - Silicon Carbide - Zinc | <ul style="list-style-type: none"> - Cement - Glass - Lime - Misc. Carbonate Use - Soda Ash | <ul style="list-style-type: none"> - Pulp & Paper | <ul style="list-style-type: none"> - Electronics Mfg. - Fluorinated GHG Production - HCFC-22 Prod./HFC-23 Destruction - Pre-Charged Equipment Import/Export - Industrial Gas Suppliers |
| Petroleum & Natural Gas Systems | | | Fuel Suppliers | | | Carbon Capture & Sequestration | Mining | |
| <ul style="list-style-type: none"> - Onshore Production - Offshore Production - Natural Gas Processing - Natural Gas Transmission/Compression - Natural Gas Distribution - Underground Natural Gas Storage - Liquefied Natural Gas Storage - Liquefied Natural Gas Import/Export | | | <ul style="list-style-type: none"> - Coal-Based Liquid Fuels Suppliers - Natural Gas and Natural Gas Liquids Suppliers - Petroleum Product Suppliers | | | <ul style="list-style-type: none"> - Geologic Sequestration of CO₂ - Injection of CO₂ - CO₂ Suppliers | <ul style="list-style-type: none"> - Underground Coal Mines | |
| | | | | | | | Direct Emitters Suppliers CO ₂ Injection | |


Data Publication



- Data publication tool allows stakeholders and the public to access the key data elements quickly and easily and to sort data by location, sector, and by gas
- GHGRP data available at: <http://ghgdata.epa.gov>



GHGRP RY 2010 Data Summary: Emissions by Facility and Sector




RY 2010 data presented here reflects data reported to the GHGRP as of April 6, 2012

Subparts Related to CCS



- Subpart PP – Suppliers of CO₂ (capture facilities)
- Subpart UU – Injection of CO₂
- Subpart RR – Geologic Sequestration of CO₂




Subpart PP –Suppliers of CO₂




- The Subpart PP source category includes facilities that capture a CO₂ stream for supplying to the economy or injecting underground
 - CO₂ capture (ethanol, natural gas processing, etc)
 - CO₂ production wells (extraction)
- Over 120 facilities reported data for 2010

Subpart PP Capture and Extraction Facilities
CO₂ Supplied in 2010




Subpart PP Capture and Extraction Facilities
CO₂ Supply End Uses in 2010



* Source: EPA Greenhouse Gas Reporting Data. Based on reporting year 2010 data.

MMt = million metric tons; Mt = metric tons

Subpart PP - Facilities



Subpart UU – Injection of CO₂



- The Subpart UU source category includes facilities with any well or group of wells that inject a CO₂ stream into the subsurface (and that do not report under Subpart RR)
 - UIC Class II, enhanced oil and gas recovery (EOR) projects
 - Projects that received an R&D exemption from Subpart RR
 - Other facilities injecting CO₂ (e.g., acid waste disposal, gas plants)
- Annually reported data includes:
 - the amount of CO₂ received for injection
 - data used to calculate the amount
 - the source of CO₂ (if known)
- Data collection began in 2011 and the 1st reports were submitted to EPA in September 2012

Subpart RR – Geologic Sequestration of CO₂



- The Subpart RR source category includes:
 - Any well or group of wells that inject a CO₂ stream for long-term containment in subsurface geologic formations
 - All wells permitted as UIC Class VI wells
- Facilities that conduct enhanced oil and gas recovery are **not** required to report geologic sequestration under Subpart RR unless:
 - The owner or operator chooses to opt-in to Subpart RR, or
 - The facility holds a UIC Class VI permit for the well or group of wells used to enhance oil and gas recovery
- All facilities subject to Subpart RR must develop and implement an EPA-approved monitoring, reporting and verification (MRV) plan
- Subpart RR is complementary to and builds on UIC requirements

Subpart RR - R&D Project Exemption



- R&D projects may receive an exemption from Subpart RR provided they meet the eligibility requirements
- A project is eligible for the exemption if it meets the Subpart RR definition of R&D project:
 - *“a project for the purpose of investigating practices, monitoring techniques, or injection verification, or engaging in other applied research, that will enable safe and effective long-term containment of a CO₂ stream in subsurface geologic formations, including research and short duration CO₂ injection tests conducted as a precursor to long-term storage”*
- R&D projects that are exempt from Subpart RR **are** required to report under Subpart UU*


* Unless the R&D Project also meets the separate definition of exempt “research and development” under 40 CFR Part 98, Subpart A

Subpart RR - Data Collection and Reporting Requirements



- The following quantities are required to be reported annually:
 - CO₂ received
 - CO₂ injected
 - CO₂ produced
 - CO₂ emitted by surface leakage
 - CO₂ emitted from equipment leaks
- These quantities (with the exception of CO₂ received) are used to calculate the amount of CO₂ sequestered, which is reported annually and cumulatively over the Subpart RR reporting lifetime of the facility.
- The source of the received CO₂, if known, must also be reported.
- Facilities must submit an annual monitoring report, which includes: a narrative history of monitoring efforts; non-material changes to MRV Plan; a narrative history of monitoring anomalies; and a description of surface leakage of CO₂, if any

Illustrative Example of GHGs to be Reported for Subpart RR



M = Meter
EL&V = Equipment Leaks
and Vented Emissions

Subpart RR - MRV Plan: Major Elements




1. Delineation of the maximum monitoring area (MMA) and active monitoring areas (AMAs)
2. Identification of potential surface leakage pathways for CO₂ in the MMA
3. A strategy for detecting and quantifying surface leakage of CO₂
4. A strategy for establishing the expected baseline for monitoring CO₂ surface leakage
5. Site-specific variables for the mass balance equation

Monitoring Areas



Subpart RR Maximum Monitoring Area (MMA) boundary defined by **presence of Free Phase CO₂ until the plume has stabilized, plus a one-half mile all around buffer**




Buffer Zone
($\frac{1}{2}$ mile)

Subpart RR Active Monitoring Area (AMA) boundary defined by **the area that will be monitored over a specific time interval**

☼ = CO₂ Injection
● = Abandoned Well

Illustration of GS Site Monitoring Detection, Verification, Quantification



Source: Lawrence Berkley
National Laboratory (LBNL)

Strategy for Establishing Baselines



Primary goal: to discern whether or not the results of monitoring are attributable to leakage of injected CO₂

- Includes environmental and operational parameters
- Approaches should be: reliable, representative of site conditions, and accurate enough to minimize false (+/-) readings
- Methods that can be used to establish expected baselines
 - Pre-injection monitoring of environmental variables
 - Contemporaneous monitoring (reference or control location(s))
 - Use of predictive models

For More Information



GHG Reporting Program:
<http://www.epa.gov/ghgreporting/>



Published Data:
<http://ghgdata.epa.gov>

ghgdata

Resources by Subpart (i.e., PP, UU, RR):
<http://www.epa.gov/ghgreporting/reporters/subpart/index.html>